

Chongqing JERI Marine Equipment Co.,Ltd.

Address: No 6, 24 floor, shimahe street, jiangbei, chongqing

Tel: +86-23-67023103; Mobile: +86-17723269020

E-mail: info@jeri-marine.com http://www.jeri-marine.com

High-build Epoxy Drinking Water Tank Anticorrosive Primers (Acquired the certification of America FDA)

Characteristics: Coating film innoxious, excellent resistance ofwater, oil, corrosion, abrasion, good adhesion, high-build constructive property, firmed paint film.

Uses: Use for water chamber \(\) drinkin water cabin \(\) distilled water cabin, alos can be use for the anticorrosion of drinking water pipeline inside.

Technical target:

Mixing ratio: Host crystal/Firming agent=6/1(by weight)

Standard film thickness: Dry: 100μm/coat

Academic spreading rate: 0.22 kg/ m2/100µm

Solid contents: 78%

Humidity requirement: below 85%

Drying time & Coating interval

Temperature ℃	-10	0	10	20	30
Dry to touch (hrs)	4	2.5	2	1.5	1
Dry semi-hard (hrs)	36	24	14	10	8
Min. interval (hrs)	36	24	14	10	8

Substrate treatment: Remove rust and oxide skin by abrasive blasting, reached ISO Sa2.5 grade Matching:

Applicable substrate: Unpainted steel

Applicable upper coatings: High-build Epoxy Drinking Water Tank Anticorrosive Paint (Acquired the

certification of America FDA)